



Bearing import and Export Co., Ltd



65 mm x 140 mm x 33 mm SKF 7313 BECBY
angular contact ball bearings

Bearing No. 7313 BECBY

7313 BECBY Bearing 2D drawings and 3D CAD models

Size	140x65x33 mm
Bore Diameter	140 mm
Outer Diameter	65 mm
Width	33 mm
d	65 mm
D	140 mm
B	33 mm
d ₁	94.15 mm
d ₂	78.45 mm
D ₁	112.85 mm
a	60 mm
r _{1,2} - min.	2.1 mm
r _{3,4} - min.	1.1 mm
d _a - min.	77 mm
D _a - max.	128 mm
D _b - max.	133 mm
r _a - max.	2 mm
r _b - max.	1 mm
Basic dynamic load rating - C	108 kN
Basic static load rating - C ₀	80 kN
Fatigue load limit - P _u	3.4 kN
Reference speed	5600 r/min
Limiting speed	5600 r/min
Calculation factor - k _r	0.1



Bearing import and Export Co., Ltd

Calculation factor - k_a	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	52.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.14
EAN	7316576650772
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric



Bearing import and Export Co., Ltd

Long Description	65MM Bore; 140MM Outside Diameter; 33MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7313 BECBY
Weight / LBS	4.722
Outside Diameter	5.512 Inch 140 Millimeter
Bore	2.559 Inch 65 Millimeter
Width	1.299 Inch 33 Millimeter
bore diameter:	65 mm
radial static load capacity:	80 kN
outside diameter:	140 mm
cage material:	Brass
overall width:	33 mm
outer ring width:	33 mm
contact angle:	40 °
maximum rpm:	5600 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2 mm



Bearing import and Export Co., Ltd

radial dynamic load capacity:	108 kN
series:	73
d_1	94.15 mm
d_2	78.45 mm
D_1	112.85 mm
$r_{1,2}$ min.	2.1 mm
$r_{3,4}$ min.	1.1 mm
d_a min.	77 mm
D_a max.	128 mm
D_b max.	133 mm
r_a max.	2 mm
r_b max.	1 mm
Basic dynamic load rating C	116 kN
Basic static load rating C_0	86.5 kN
Fatigue load limit P_u	3.65 kN
Calculation factor A	0.112
Calculation factor k_r	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	2.15 kg